

This Double Hinge Flap Valve is of a circular aperture design which prevents reverse flow in outfall installations. Suitable for use in surface or storm water applications. Typical installations include outfalls from treatment works & rivers, etc. All valve sizes are double hung to provide optimal sealing. For salt water application please call our sales office.

Main Features

- Tamper-proof stainless steel hinge pins
- Body and flap manufactured from ductile iron
- Incorporates flap lifting eye to facilitate opening
- Superior metal seat facing machined to a high quality finish providing excellent seating characteristics
- Unique lightweight ductile iron design providing ease of handling and installation
- Single link design for sizes DN80-250 – double link design for sizes DN300 – 600
- Corrosion resistant construction coated in fusion bonded epoxy, minimum thickness 300 microns
- Drilled to suit both wall or flange mounting
- Bolt sets ordered separately depending on application – please phone our sales department for details

Code	DN	A	B	C	PCD	Bolts	hole dia	Weight kg
DU5080	80	200	225	125	160	4	18	5
DU5100	100	220	245	135	180	4	18	6
DU5150	150	285	315	172	240	4	22	11
DU5200	200	332	368	202	295	4	22	16
DU5225	225	368	404	220	324	4	18	20
DU5250	250	400	438	238	355	4	26	23
DU5300	300	454	495	268	410	4	26	32
DU5350	350	550	588	313	470	4	26	34
DU5375	375	550	588	313	495	4	25	34
DU5400	400	580	612	322	525	4	30	49
DU5450	450	585	635	360	585	4	31	56
DU5500	500	600	692	392	650	4	34	68
DU5600	600	730	815	450	770	4	37	93



Double Link

Single Link

